

Section 1 - Identification Of Chemical Product And Company

Hickey & Co Pty Ltd
71-77 Audley St
Petersham, NSW 2049

Phone: 02 9564 1888
Fax: 02 9550 9339

Substance: Acrylic ester.
Trade Name: Aron Alpha
Product Use: Adhesive.
Creation Date: December, 2002
Revision Date: February, 2008

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of ASCC Australia.

Not a Dangerous Good according to the Australian Dangerous Goods (ADG) Code.

Risk Phrases: R36/37/38. Irritating to eyes, respiratory system and skin.

Safety Phrases: S2, S23, S26, S38, S24/25. Keep out of reach of children. Do not breathe vapour. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

SUSDP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good.

UN Number: None allocated

Emergency Overview

Physical Description & colour: Clear, colourless liquid.

Odour: Sharp odour.

Major Health Hazards: irritating to eyes, respiratory system and skin.

Potential Health Effects

This product bonds instantly under pressure. If it bonds to skin, it may be very difficult to release. If this happens, seek medical attention. Solvents such as acetone (nail polish remover) may be helpful.

Inhalation

Short term exposure: Available data indicates that this product is not harmful. However product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short term exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short term exposure: Available data shows that this product is not harmful. However product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short term exposure: It is almost impossible to swallow this product as it solidifies on contact with saliva. Saliva will lift adhesive in 1-2 days. Avoid swallowing adhesive after detachment.

Long Term exposure: No data for health effects associated with long term ingestion.

MATERIAL SAFETY DATA SHEET

Carcinogen Status:

ASCC: No significant ingredient is classified as carcinogenic by ASCC.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc, %	TWA (mg/m ³)	STEL (mg/m ³)
Ethyl 2-cyanoacrylate	7085-85-0	>98	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 20 minutes or until chemical is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts). If irritation persists, repeat flushing and obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

Eye Contact: Quickly and gently blot or brush away product. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water until the product is removed or until a few minutes after irritation has ceased, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face.

If eyelids have been bonded shut, seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: This product is classified as a C1 combustible product. There is a slight risk of an explosion from this product if commercial quantities are involved in a fire. Vapours from this product are heavier than air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. They may also flash back considerable distances.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: Preferred extinguishing media are carbon dioxide, dry chemical, foam, water fog.

Fire Fighting: When fighting fires involving significant quantities of this product, wear a splash suit complete with self contained breathing apparatus.

Flash point: 83°C

Upper Flammability Limit: No data.

Lower Flammability Limit: 1.7%

Autoignition temperature: No data.

Flammability Class: C1

Section 6 - Accidental Release Measures

Accidental release: In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including face mask, face shield and gauntlets. All skin areas should be covered. See above under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Sweep up and shovel or collect recoverable product into

MATERIAL SAFETY DATA SHEET

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose violently under normal storage conditions, but may set over time. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Protect this product from light.

Incompatibilities: water, bases, amines, alcohol.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Occasionally hydrogen cyanide gas. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death. Hydrogen cyanide poisoning signs and symptoms are weakness, dizziness, headache, nausea, vomiting, coma, convulsions, and death. Death results from respiratory arrest. Hydrogen cyanide gas acts very rapidly; symptoms and death can both occur quickly.

Polymerisation: Polymerized by contact with water, alcohols, amines, alkalies. Polymerisation is also initiated by pressure - it is an "instant glue". Also may slowly set (polymerise) when heated, or when exposed to sunlight.

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
No hazardous ingredients present in hazardous concentrations.	

Section 12 - Ecological Information

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

Section 13 - Disposal Considerations

Disposal: Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Please do NOT dispose into sewers or waterways.

Section 14 - Transport Information

ADG Code: This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: This product was found in the public AICS Database.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
AICS	Australian Inventory of Chemical Substances
CAS number	Chemical Abstracts Service Registry Number
Hazchem Number	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
ASCC	Office of the Australian Safety and Compensation Council
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSDP	Standard for the Uniform Scheduling of Drugs & Poisons
UN Number	United Nations Number

MATERIAL SAFETY DATA SHEET

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the ASCC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2001(2003)]
Copyright © Kilford & Kilford Pty Ltd, February, 2008.

<http://www.kilford.com.au/> Phone (02)9251 4532